

SOLDER PIN SERIES

Series	Voltage Range [V]	Temperature Range [°C]	Case Φ xH [mm]	Expected Lifetime [hrs]	Applications
ARC/S STANDARD	200	-40° +85° Self extinguishing construction and electrolyte	30x40 45x100	2.000 hrs	Solder pin mounting Industrial application High reliability 2-4 pins configuration
AKS 4/5 pins	40 - 450	-40° +85° Self extinguishing construction and electrolyte	30x40 40x100	5.000 hrs	Solder pin mounting Industrial applications
ACC ACS STANDARD APPLICATIONS	25 - 500	-40° +85° Self extinguishing construction and electrolyte	30x40 45x100	5.000 hrs	Snap-in type, Industrial application High reliability 2-4 pins configuration
AZK 4/5 pins	200 - 450	-40° +105°	30x40 40x100	5.000 hrs	Solder pin mounting Solar and wind application Energy Storage
AZC AZS STANDARD APPLICATIONS	200 - 450	-40° +105°	30x40 40x100	5.000 hrs	Solder pin mounting Industrial applications
ATK 4/5 pins	160 - 450	-55° +105°	30x40 40x100	8.000 hrs	Long life Low ESR Solar and wind application
ATC ATS PROFESSIONAL APPLICATIONS	200- 450	-55° +105°	30x40 40x100	8.000 hrs	Very Long life Low ESR Solar and wind application

